charge. fast. anywhere. The flexible Wallbox.



NRGkick

flexible wallbox for electric vehicles Product data sheet





Product information

Absolute safety

NRGkick is the safest loading unit on the market. It offers a wide range of safety features such as temperature monitoring on each plug attachment and phase pin, overheating protection, blackout protection, undervoltage protection and overvoltage protection, phase shift detection, false connection test, switching contact diagnosis, protective conductor test by means of loop impedance measurement, included residual current protection (AC, DC + 6 mA) and much, much more!

Full connectivity

Via Bluetooth, WLAN, NRGkick Cloud and the Web API, NRGkick is always and everywhere accessible. Optionally, the intelligent charging unit offers connectivity via GSM/GPS/ SIM. Here, the connection is made via EDGE, GPRS as well as 4G M1 and 4G NB-IoT and is thus equipped for the requirements of the Internet of Things.

Intelligent Features

The multitude of functions makes NRGkick arguably the most intelligent loading unit on the market, offering among others: Automatic charging reports, locally assignable charging reports via WLAN, display of charging current costs, time-controlled charging, upgradeability, photovoltaic-guided charging, optional OCPP, grid-serving control capability, autonomous Load Management, Charging4Fleets....

Highest Quality

NRGkick was the first mobile charging unit ever to be validated and certified by VDE and ÖVE. However, not only NRGkick itself, but also the production meets the highest standards. Therefore, the manufacturing and production facility is also certified by VDE and ÖVE and continuously production monitored.









Technical data

Type name NRGkick

Nominal voltage

Nominal current

Maximum charging power 22 kW

RCD (AC) 30mA

RCD (DC) 6mA

IP protection class IP67, IP69K

Charge mode

Mode 2 according to IEC EN 62752 Mode 3 when using attachment Type 2 Weight 5m variant approx. 3,86 kg

CE compliance

CE compliant to UKCA compliant to IEC EN 62752, IEC EN 62196, IEC EN 60309

Operating conditions

-40°C.... +70°C (standard: +45°C) 5% - 95% humidity max. 4.000m above sea level

Dimensions (L, W, H) 216mm x 90mm x 64mm

Connection technology

Bluetooth Low Energy (BLE), WiFi; Optional: GSM- und GNSS-interface (GSM: EDGE, GPRS, 4G M1, 4G NB-IoT; GNSS: GPS, GLONASS, Galileo, Baidou)

